

# AQUAOXY

*Flexible oxygen supply for ponds*



- Suitable for ponds up to 50 m<sup>3</sup> or with high fish stock
- Special safe 12 volt technology for AquaOxy 1000 – 2000
- Optimal oxygen supply for pond flora and fauna
- Robust motor and high-quality UV-stabilised housing
- Reduced noise, energy-efficient operation
- Flexible location thanks to adequate hose length
- Easy and convenient handling
- Included in the scope of delivery: Air stones and replacement membrane set

**From AquaOxy 1000**

- Air stones are wear-free
- Infinitely adjustable air outflow rate

**AquaOxy 4800**

- Crafted with a high quality aluminium housing
- Can be used as an ice preventer



		AquaOxy 250	AquaOxy 500	AquaOxy 1000	AquaOxy 2000	AquaOxy 4800
Dimensions (L x W x H)	mm	167 x 106 x 75	185 x 140 x 110	220 x 225 x 135		245 x 185 x 200
Rated voltage (primary, secondary)		-		230 V / 50 Hz, 12 V / AC		-
Rated voltage		230 V / 50 Hz		-		220 - 240 V / 50/60 Hz
Power consumption	W	4	8	15	25	60
Power cable length	m	3.00		2.00 (Power unit) + 3.00		5.00
Guarantee <sup>1P, 173</sup>	Years	2				
Max. flow rate	l/h	250	500	1000	2000	4800
Pressure		0.15 / 1.50		0.2 / 2.00		0.25 / 2.50
Mechanical adjustment		No			Yes	
Hose (quantity / length / diameter)		1 UNIT / 10 m / 4.5 mm		2 pc / 5 m / 4.5 mm		4 pc / 5 m / 4.5 mm
Number of outlets	Unit	1		2		4
Suitable for ponds up to max.	m <sup>3</sup>	3.0		10.0		50.0
Outdoor suitability		Unlimited				splash resistant
Number of air stones	Unit	1		2		4
Item no. (GB-Version)		73377	57567	-	57437	73378
Item no.		34064	57063	37125	57350	50398